MITSUBISHI HEAVY INDUSTRIES

Residential Air-Conditioners Catalogue for Europe

SR series

2026



MOVE THE WORLD FORWARD MITSUBISHI HEAVY INDUSTRIES GROUP



SINGLE-SPLIT FLOOR STANDING TYPE

SRF-ZS/ZSX



SRF25,35ZS-W, 50ZSX-W

Auto air outlet selection

In case both lower and upper air outlets can be selected.





Wireless remote control



SRC25,35ZS-W2




SRC50ZSX-W2,-W3

KEY FEATURES

- The elegant semi-flat front panel in stylish white complements various room aesthetics and creates a relaxing atmosphere
- Offers options for wall hanging, floor standing, or behind-gallery installation
- Utilizes refrigerant R32 for low Global Warming Potential (GWP) and high energy efficiency
- Operates quietly with a noise level as low as 25dB(A) in cooling ULo mode
- Includes a "flap control system" allowing users to adjust flap angles and positions according to their preference
- Equipped with an allergen-clear filter as a default feature

Installation workability

Piping and drain hose connection can be selected out of 6-directions.



SPECIFICATIONS

Indoor unit				SRF25ZS-W	SRF35ZS-W	SRF50ZSX-W
Outdoor unit				SRC25ZS-W2	SRC35ZS-W2	SRC50ZSX-W2,-W3
Power source				1 Phase, 220 - 240V, 50Hz		
Nominal cooling capacity (Min-Max)			kW	2.5 (0.9 - 3.1)	3.5 (0.9 - 4.1)	5.0 (1.1 - 5.6)
Nominal heating capacity (Min-Max)			kW	2.9 (0.8 - 3.7)	4.5 (0.8 - 5.2)	6.0 (0.8 - 7.4)
Power consumption		Cooling/Heating	kW	0.59 / 0.66	0.82 / 1.12	1.32 / 1.58
EER/COP		Cooling/Heating		4.24 / 4.39	4.27 / 4.02	3.79 / 3.80
Max. running current			A	9	9	15
Sound power level	Indoor	Cooling/Heating	dB(A)	50 / 51	51 / 52	58 / 58
	Outdoor	Cooling/Heating		59 / 60	63 / 64	63 / 62
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	dB(A)	38 / 32 / 29 / 25	40 / 35 / 33 / 29	46 / 38 / 33 / 28
		Heating (Hi/Me/Lo/Ulo)		39 / 35 / 33 / 29	41 / 36 / 35 / 33	46 / 41 / 38 / 32
	Outdoor	Cooling/Heating		45 / 47	50 / 51	51 / 51
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	m^3/min	9.0 / 7.6 / 6.7 / 5.8	9.2 / 7.8 / 7.3 / 6.4	11.5 / 9.6 / 7.4 / 6.6
		Heating (Hi/Me/Lo/Ulo)		10.5 / 8.2 / 7.7 /6.6	10.7 / 8.3 / 8.1 / 7.4	12.0 / 10.0 / 9.4 / 7.6
	Outdoor	Cooling/Heating		27.4 / 27.4	31.5 / 31.5	39.0 / 33.0
Exterior dimensions	Indoor	Height x Width x Depth	mm	600 x 860 x 238		
	Outdoor			540 x 780(+62) x 290		640 x 800(+71) x 290
Net weight	Indoor / Outdoor		kg	18.0 / 31.0	19.0 / 34.5	19.0 / 45.0
Refrigerant		Type/GWP		R32 / 675		
		Charge	kg/TCO$_2$Eq	0.62 / 0.419	0.78 / 0.527	1.30 / 0.878
Refrigerant piping size		Liquid/Gas	ø mm	6.35(1/4") / 9.52(3/8")		6.35(1/4") / 12.7(1/2")
Refrigerant line (one way) length [chargeless length]			m	Max.20 [10]	Max.20 [15]	Max.30 [15]
Vertical height differences		Outdoor is higher/lower	m	Max.10 / Max.10		Max.20 / Max.20
Outdoor operating temperature range		Cooling	˚CDB	-15 to 46		
		Heating		-15 to 24		
Clean filter				Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1		

- The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27˚CDB, 19˚CWB, and outdoor temp. of 35˚CDB. Heating: Indoor temp. of 20˚CDB, and outdoor temp. of 7˚CDB, 6˚CWB.
- Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
- 'tonne(s) of CO_2 equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.