MITSUBISHI HEAVY INDUSTRIES

Residential Air-Conditioners Catalogue for Europe

SR series

2026



MOVE THE WORLD FORWARD MITSUBISHI HEAVY INDUSTRIES GROUP



New

Wall mounted

ZT series

The overall design is simple and box-like, with a flat front surface that matches well with modern interiors.

The smooth front panel flows gently from the top to the front, like a soft veil.

Tapered edges soften the overall form. The front panel is precisely aligned with edge lines that extend in three directions, contributing to a polished appearance.

A soft yet solid design

A soft impression reminiscent of a veil



ZT series

Design



Black
for a bold, modern look

Colour variations

The unit is available in three colour variations.
Choose the one that best suits your interior style.

Pure White
a clean, classic finish



Titanium & Black
offering a sophisticated, metallic edge





Craftsmanship in details





The screws of the unit are concealed beneath a cover, giving the unit a less mechanical and more refined, interior-oriented appearance.



One of the edges lines is aligned with the upper flap, forming a single smooth, clean line from the wall across the unit.

Jet black outdoor unit

Alongside the harmonious white that blends into its surroundings, there is now a black outdoor unit, providing a bold and sophisticated presence that enhances its surroundings.



SRC20/25/35ZT-WB



SRC50ZT-WB



SRC20/25/35ZT-W



SRC50ZT-W





R32

SINGLE-SPLIT WALL MOUNTED TYPE

Premium Series

SRK-ZT-WF

New



SRK20,25,35,50ZT-WF

Pure White(-WF)

Wireless Control System

BUILT IN WIRELESS LAN



Black(-WFB)



Titanium & Black(-WFT)



Wireless remote control

KEY FEATURES

- Elegant, timeless design, ideal for small to medium-sized living spaces
- Available in three different colour preferences
- R32 environmentally friendly refrigerant offers low Global Warming Potential (GWP) and high energy efficiency
- Jet technology ensures quiet air flow and extended reach
- Wireless interface control is integrated as standard

SPECIFICATIONS

Indoor unit				SRK20ZT-WF,-WFB,-WFT	SRK25ZT-WF,-WFB,-WFT	SRK35ZT-WF,-WFB,-WFT	SRK50ZT-WF,-WFB,-WFT
Outdoor unit				SRC20ZT-W,-WB	SRC25ZT-W,-WB	SRC35ZT-W,-WB	SRC50ZT-W,-WB
Power source				1 Phase, 220 - 240V, 50Hz			
Nominal cooling capacity (Min-Max)			kW	2.0 (0.9 - 2.9)	2.5 (0.9 - 3.3)	3.5 (0.9 - 4.0)	5.0 (1.3 - 5.4)
Nominal heating capacity (Min-Max)			kW	2.7 (0.9 - 4.5)	3.2 (0.9 - 4.7)	4.0 (0.9 - 5.0)	5.8 (1.3 - 6.4)
Power consumption		Cooling/Heating	kW	0.42 / 0.53	0.57 / 0.70	0.88 / 0.91	1.43 / 1.48
EER/COP		Cooling/Heating		4.76 / 5.09	4.39 / 4.57	3.98 / 4.40	3.50 / 3.92
Max. running current			A	9	9	9	14.5
Sound power level	Indoor	Cooling/Heating	dB(A)	47 / 49	50 / 52	52 / 55	59 / 59
	Outdoor	Cooling/Heating		55 / 56	56 / 58	62 / 61	63 / 63
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	dB(A)	32 / 25 / 22 / 19	35 / 28 / 23 / 19	38 / 30 / 26 / 19	45 / 36 / 29 / 22
		Heating (Hi/Me/Lo/Ulo)		34 / 29 / 23 / 19	38 / 30 / 24 / 19	40 / 36 / 25 / 19	44 / 37 / 31 / 24
	Outdoor	Cooling/Heating		42 / 43	45 / 46	50 / 48	50 / 51
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	m^3/min	9.0 / 7.0 / 5.9 / 5.0	10.0 / 8.3 / 6.0 / 5.0	10.0 / 8.6 / 6.3 / 5.0	13.3 / 10.0 / 7.6 / 5.7
		Heating (Hi/Me/Lo/Ulo)		9.4 / 8.4 / 6.4 / 5.3	10.6 / 9.0 / 6.5 / 5.3	11.3 / 10.0 / 6.7 / 5.3	13.5 / 10.6 / 8.8 / 6.6
	Outdoor	Cooling/Heating		21.8 / 21.8	23.3 / 25.3	29.9 / 26.4	29.8 / 29.8
Exterior dimensions	Indoor	Height x Width x Depth	mm	290 x 870 x 230			
	Outdoor			540 x 780(+62) x 290			595 x 780(+62) x 290
Net weight	Indoor / Outdoor		kg	10.5 / 33.0		11.0 / 33.5	11.0 / 33.0
Refrigerant		Type/GWP		R32 / 675			
		Charge	kg/TCO$_2$Eq	0.76 / 0.513		0.81 / 0.547	0.83 / 0.560
Refrigerant piping size		Liquid/Gas	ø mm	6.35(1/4") / 9.52(3/8")			6.35(1/4") / 12.7(1/2")
Refrigerant line (one way) length [chargeless length]			m	Max.20 [15]			Max.25 [15]
Vertical height differences		Outdoor is higher/lower	m	Max.15 / Max.15			Max.20 / Max.20
Outdoor operating temperature range		Cooling	°CDB	-15 to 50			
		Heating		-20 to 24			
Clean filter				Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1			

- The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level indicates the value in an anechoic chamber.During operation these values are somewhat higher due to ambient conditions.
- 'tonne(s) of CO_2 equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.



Remote control

- A simple and intuitive design for effortless use
- Temperature controlled in precise 0.5˚C increments
- Enhanced visibility with back-light for easy reading







SRC20,25,35ZT-WB



SRC20,25,35ZT-W



SRC50ZT-WB



SRC50ZT-W

Craftsmanship in details

- The screws are concealed beneath a cover, giving the unit a less mechanical and more refined, interior-oriented appearance.



- One of the edges lines is aligned with the upper flap, forming a single smooth, straight line from the wall across the unit.



Jet black outdoor unit

- Available in a jet black colour variation, providing a bold and sophisticated presence that enhances its surroundings.



